



PAVEFIX

Quick fix and long term performance



Pavefix is a convenient, easy to use instant pothole repairer ideal for asphalt and concrete surfaces.

Pavefix will immediately and permanently repair large cracks or potholes in motorways, aircraft pavements, roads, car parks, driveways and all the trafficable areas.

FEATURES AND BENEFITS

- Pavefix is a combination of selected aggregates (granite or basalt) combined with a special proprietary binder
- Requires no mixing, heating or priming
- Priming is recommended if used with concrete surfaces
- It can be applied in dry or wet conditions straight from the bucket with ease
- No compaction device necessary – Hand compaction with the back of the shovel is sufficient
- The area can be immediately opened to traffic.

APPLICATION

1. All loose debris, standing water is brushed out of the pothole, large crack or depression;
2. Sufficient Pavefix is placed to slightly overfill the hole;
3. The Pavefix in the pothole is then compacted with the back of a shovel or a tamper if available.



For deep potholes, a 15mm layer of Pavefix can be applied at the bottom of the hole, followed by a layer of suitable aggregate such as 10mm which is then compacted. Pavefix is being used to top off the layer in the pothole.

TECHNICAL DATA

For detailed technical information on the product please refer to the Pavefix Technical Bulletin which is available from SAMI Bitumen Technologies.



SAMI BITUMEN TECHNOLOGIES

2, 3-5 Gibbon Road, Winston Hills, NSW 2153, Australia

T: +61 2 9624 0100

F: +61 2 9624 0190

www.sami.com.au

Whilst every care is taken in the preparation of this data sheet, no responsibility is accepted for the interpretation of information contained herein, nor is any warranty expressed or implied for the suitability of the material for a particular application.