

PRODUCT DATA SHEET



PRODUCT NAME: AMC Bitumen Cutbacks

DESCRIPTION

AMC bitumen cutback grades are blends of bitumen and suitable solvents formulated to be used for priming, primer sealing and sealing applications.

AMC grades range and applications

AMC Grade (AS2157)	% Kerosene (vol.at 15°C)	Class	Application	Recommended application rate (L/m ²)
AMC00	56	Primer	Low porosity base courses	0.25 – 0.35
AMC0	44	Primer	Medium porosity base courses	0.30 – 0.60
AMC1	34	Primer	High porosity base courses	0.60 – 1.0
AMC2	27	Primer seal	Low porosity base courses	0.7 – 1.2
AMC3	21	Primer seal	Medium porosity base courses	0.8 – 1.4
AMC4	16	Primer seal	High porosity base courses	0.9 – 1.6
AMC5	11	Seal	Cool climate sealing	1.2 – 1.8
AMC6	7	Seal	Medium climate sealing	1.2 – 1.8
AMC7	3	Seal	Hot climate sealing	1.2 – 1.8

STORAGE, HANDLING & USAGE

- All the AMC grades contain a solvent carrier and the outmost care in storage and handling this class of material should be observed; they should be stored in sheltered areas (away from the sun);
- Care must be taken in order to prevent the product entering sewage or storm-water systems;
- The surface to be treated has to be free of debris prior to application.

AVAILABILITY

Available in 200 L drums or bulk (minimum 6 tonnes) on order in all the States and Territories.