

PRODUCT DATA SHEET



PRODUCT NAME: Pavefix

DESCRIPTION

Pavefix is a cold mix bituminous material for the instant repair of potholes, small utility trenches, depressions in asphalt and concrete for motorways, airfields, roads, carparks, driveways and all trafficable areas. Pavefix consists of a combination of selected aggregates blended with a proprietary binder.

FEATURES

- The material is handled and applied cold;
- No mixing is required;
- No priming is necessary;
- There is no 'pick up' or shrinkage;
- No necessity to cut out;
- Can be applied in wet conditions;
- A single person operation.

STORAGE, HANDLING & USAGE

- Preferably store in a sheltered environment with temperatures of 10°C or higher;
- Shelf life is 9 to 10 months (partly used pails must be tightly sealed);
- Prior to the application, brush out loose debris, standing water, oil etc. from the pothole, trench or depression and pour in sufficient Pavefix to slightly overfill. Compact with the back of a shovel or tamper. The repair may be immediately trafficked;
- Pavefix may be applied in extremes of temperature and in wet conditions;
- For very deep holes apply a layer of Pavefix (about 15 - 20 mm deep) in the pothole, followed by a layer of single graded aggregate (6 - 10mm in size). Thoroughly compact the aggregate and then top off with a 20 - 30 mm layer of Pavefix as a wearing surface and compact;
- The stability of the applied and compacted Pavefix develops fully within 24 hours;
- Pavefix can be trafficked immediately without any pick up.

RESISTANCE TO VARIOUS CHEMICAL AGENTS

Diluted acids/alkalis	Good
Mineral/vegetable oils	Good
Grease	Will tend to soften with exposure to grease but not significantly
Petroleum solvent	Not resistant
Methylated spirits	Resistant

AVAILABILITY

Pavefix is available in 20kg pails on order in all the States and Territories.